



Elevating and Amusement Devices Safety Division	Ref. No.: 297 / 22
GUIDELINE	Date: June 10, 2022

IN THE MATTER OF:

THE TECHNICAL STANDARDS AND SAFETY ACT 2000,
S.O. 2000, c. 16

- and -

ONTARIO REGULATION 209/01 (Elevating Devices) made under the
Technical Standards and Safety Act, 2000

- and -

the Elevating Devices Code Adoption Document dated June 1, 2001, as amended
by ED CAD 295/21

**Subject: Alteration Guideline and Alteration Checklist for CSA B355:19 Platform lifts and
stair lifts for barrier-free access (as amended by 295 / 22)**

Distribution: Posted on TSSA website

1. Effective Date

- 1.1 This Directors Guideline becomes effective August 1, 2022 and is to be used in conjunction with alterations performed under the **CSA B355:19 Platform lifts and stair lifts for barrier-free access**, as adopted in Code Adoption Document (CAD) Amendment 295 / 22.

2. Introduction

- 2.1 The purpose of this Director's Guideline, in conjunction with Code Adoption Document (CAD) Amendment 295 / 22, is to:
- (a) advise which types of upgrades are classified as alterations;
 - (b) indicate the format of the design submission required (see O.Reg 209/01 s.15), by categorizing the scope of work as "major", "minor A" or "minor B";
 - (c) provide instruction on the use and submittal of the alteration checklist;
 - (d) provide a summarized list of requirements associated with a given alteration scope via a checklist;
 - (e) supplement the adoption of Annex D in **CSA B355:19 Platform lifts and stair lifts for barrier-free access** as detailed in Section 7.3 of the CAD; and
 - (f) identify compliance requirements related to any TSSA specified requirements or TSSA defined alterations.

3. Alterations

- 3.1 Work performed on an elevating device other than worked performed as maintenance, repair, or replacement is an alteration.
- 3.2 This guideline captures the Alteration requirements of 3.1 above and displays these requirements in a checklist format (refer to the Alteration Checklist for B355:19)

3.3 Type of Alteration Work

Columns 3 to 6 of the Alteration Checklist classify the type of work as one of the following types:

- (a) **Alteration: Modification / Change** (column 3)
means a change to the original design or characteristics of a component, assembly or the device as a whole, such as material, strength, size, dimension, rating, setting, function, operational mode, design parameters etc., whereby the change may be made on existing equipment or by substituting new modified equipment.
Note that a change of the component make or model, without any other change, may constitute an alteration under requirements of CAD 295 / 22 or section 7 of this guideline (see item (d) below).
- (b) **Alteration: Addition** (column 4)
means addition of a new component or a design feature, not previously provided e.g. addition of top-of-car operating devices.
- (c) **Replacement with same** (column 5)
means the substituted device, assembly or component is the same as the original and this alteration guideline defines the appropriate submission.
- (d) **Replacement with different make and model** (column 6)
means that the substituted device, assembly or component is the same as the original in its design, performance and safety characteristics, except that it is of a different make and/or model and this alteration guideline defines the appropriate submission.

*Note: In addition to the work described in 3.3 and listed in the Alteration Checklist, any other work performed on an elevating device that results in a change to the inherent safety or operational characteristics **constitutes an alteration** per 2.6.2 of the CAD, even though there may be no change in the original design. The list of alterations in the attached Alteration Checklist is not all-inclusive.*

4. Type of Design Submission

- 4.1 Columns 3, 4, 5, and 6 of the alteration checklist contains information needed to determine the type of submission required.
- 4.2 By selecting the alteration scope (see column 1 of the Alteration checklist, see also **CSA B355:19 Platform lifts and stair lifts for barrier-free access** Annex D as amended by CAD 295 / 22 or section 7 of this guideline), the submission type is identified in columns 3, 4, 5, & 6. These entries may be listed as one of the following:

Major	-	means Major alteration
Minor A	-	means Minor alteration type A
Minor B	-	means Minor alteration type B
<i>Blanks (columns 5&6)</i>	-	work that would not constitute an alteration
mrr	-	this work may proceed as a maintenance repair and replacement activity, and no submission is required
n/a	-	means TSSA has permitted an exception to a compliance requirement (for the noted alteration scope) however, if another alteration activity requires compliance, the n/a exemption no longer applies
New	-	means, not an alteration but a new installation
†	-	means that no inspection is required following the alteration
variance	-	this activity can only be considered after approval of a variance

Note: The checklist utilizes a star symbol '★' to identify TSSA designated alterations or to identify a supplemental TSSA requirement.

5. Requirements for Design Submissions and Inspections

5.1 A design submission or notification (in the case of a Minor B) must clearly specify, for each alteration covered, whether the type of the alteration work is a "modification", "addition", or "replacement".

5.2 Where multiple alterations scopes are undertaken, the "highest ranking" submission shall define the submission type.

Example: An alteration combination of Minor B and Major will be designated as a Major alteration.

5.2.1 Major Alteration:

5.2.1.1 The design submission shall be registered before the major alteration commences, except as permitted in subsection 7(2) of Ontario Regulation 209/01.

5.2.1.2 The alteration shall be inspected by TSSA prior to returning the device to service for public use.

5.2.2 Minor Alteration type A and B:

5.2.1.1 According to Section 19 of Ontario Regulation 209/01, the design submission shall be submitted for registration not later than 30 days after returning the elevating device to service. Contractors are advised to submit alteration documents in advance of the work start to ensure that no expense will be incurred should the registration of the proposed design or a requested variance be rejected.

Minor A and B alterations are permitted to be returned to service after work completion, however, the contractor who completed the alteration shall ensure that a "special inspection" has been requested within 60 days after returning the elevator to service. The contractor shall arrange and conduct any tests required by the inspector. A registered design submission or notification shall be available at the time of inspection.

5.3 Signatures

5.3.1 According to subsection 15.(6) of Ontario Regulation 209/01, all individual documents composing the design submission for any Major or Minor A alteration shall bear the **signature and seal, or electronic equivalent, of the professional engineer** who prepared or approved the design submission.

5.3.2 In the case of Minor B alterations, per Ontario Regulation 15.(9), the design submission documents (or Notification) may be signed by an officer or director of the company applying for registration if the officer or director is a mechanic or if the document is signed by a mechanic with an appropriate certificate who either performed or supervised the work to which the design submission relates.

5.3.3 Minor B's that are electronically transmitted shall be deemed acceptable provided that the signature box of the Minor B Notification form contains the name, designation and mechanic license number of a registered and licensed mechanic who supervised and is competent to oversee the scope of the minor B alteration. Example: Signature: John Smith, EDM-A, 00999999

5.4 Specification Forms

5.4.1 Alterations should be submitted on the appropriate Specification Sheets (depending on device type) and should itemize all entries that are **Directly** and **Indirectly** affected by the alteration scope.

Example: Cab Interior Modification resulting in an increase in cab weight

- Directly affected are interior finishes and flame ratings
- Indirectly affected are items such as: rope factor of safety (for electric & roped hydraulic elevators) or cylinder column strength (for hydraulic elevators)
- Sufficient details are to be provided to show compliance verification.

A list of altered components must also be summarized on the submission (typically box 4000).

5.4.2 Items which are not affected by the alterations should be noted with either:

- **N/C or No Change;** or
- The **Original Entry** followed by **Existing.** Example Car Wt.: **300 kg - Existing.**

5.4.3 Where a “major alteration” or “minor alteration” affects only a very few items, the abridged form may be used instead of the full specification form provided clarity of the submission is not compromised. The Abridged form should specify box numbers, descriptions, and new entry values.
(Example: 1670. Maximum System Pressure: 3445 kPa)

5.4.4 Some predefined templates exist for Minor B type alterations and are available from the TSSA web site. These templates shall be utilized where appropriate to ensure all relevant entries are completed and included in the submission. Multiple Minor B notification templates may be utilized to fully cover the scope of work and only one Minor B fee shall apply.

5.5 Submitting an Alteration Checklist

5.5.1 The design submission for a Major or Minor A alteration must include an Alteration Checklist to assist in demonstrating compliance with Annex D of the code as amended by CAD 295 / 22 or section 7 of this guideline. The Checklist must clearly specify the following:

- (a) The scope of the alteration shall be identified with an ‘X’ in column 0 adjacent to each column 1 item that is part of the primary scope of the alteration
- (b) All relevant sub requirements identified in column 2b shall be identified with an ‘x’ placed in column 0 to signify the sub requirement has been given engineering consideration and/or modified. Optional: If desired items which were given engineering consideration but not changed or deemed not applicable to a given installation may be marked with ‘r’ to indicate reviewed.

5.5.2 An Alteration Checklist is not required for Minor B Notifications.

5.5.3 Sections of the Alteration Checklist, which are not included in the scope of the alteration work, may be hidden (using the row-hide feature in excel) in order to display relevant alterations and suppress non-relevant alteration items.

5.5.4 To assist our clients in completing the Alteration Checklist, TSSA will post on its Website (www.tssa.org) a fillable version of the Alteration Checklist in excel format (ED-297-22.xlsx).

5.5.5 The **B355:19 reference numbers**, shown in column 1 and which are marked with ‘X’ in the Alterations Checklist, (also shown in **BOLD** font), are **those items that are required to be shown on the Alteration Data Plate** as per Annex D.2.4 of CSA B355:19 **Platform lifts and stair lifts for barrier-free access**.

5.5.6 The attached Alteration Checklist forms part of this guideline.

6 Alteration Checklist

6.1 General

6.1.1 The Alteration Checklist provides useful information to contractors, submitting engineers, reviewing engineers and inspectors to assist in determining:

- the scope of the alteration
- requirements associated with specified scope
- exemptions to a requirement (where n/a is shown)
- additional TSSA requirements (where ★ is shown)
- type of submission required (Major, Minor A or B)

6.2 Parts of the Checklist

6.2.1 Column 0:

Submitter's shall mark Column 0 with 'X' to identify the scope and applicable sub-requirements that received engineering consideration.

- Sub-requirements related to the alteration are mandatory and shall be identified with an 'x', except where the sub requirement is unrelated to the device being altered.

6.2.2 Column 1:

Column 1 contains the Alteration section numbers from **CSA B355:19 Platform lifts and stair lifts for barrier-free access** Annex D as amended by CAD 295 / 22, as well as specifically noted TSSA alterations.

TSSA designated requirements or alterations (if provided) are denoted by the ★ symbol.

6.2.3 Column 2a, 2b and 2c:

Column 2 describes the scope and applicable alteration sub requirements.

- Column 2a is the primary title of the alteration activity (e.g. interlocks)
- Column 2b is the list of sub requirements by reference number (e.g. 4.2.3)
- Column 2c is a text description of the referenced sub requirement. (e.g. Limit of travel)

6.2.4 Column 3, 4, 5 and 6:

The headings of Columns 3 to 6 define the "Type of Alteration Work" as Modification Change, Addition, Replacement with Same, and Replacement with Different. See 3.3 of this guideline.

The contents of Columns 3 to 6 define the "Type of Design Submission" as, Major Alteration, Minor A Alteration, or Minor B – Notification. See 4 of this guideline.



Roger Neate.

Director, Ontario Regulation 209/01 (Elevating Devices), appointed under the *Technical Standards & Safety Act, 2000*



Elevating and Amusement Devices Safety Division	Ref. No.: 297 / 22
Director's Order	Date: June 10, 2022

IN THE MATTER OF:

**THE TECHNICAL STANDARDS AND SAFETY ACT 2000,
S.O. 2000, c. 16**

- and -

ONTARIO REGULATION 209/01 (Elevating Devices)

- and -

the Elevating Devices Code Adoption Document dated June 1, 2001, as amended by ED CAD 295/22

**Subject: Alterations pursuant to CSA B355:19 Platform lifts and stair lifts for barrier-free access
(as amended by 295 / 22)**

Distribution: Posted on TSSA website

Pursuant to s.14(1) of the *Technical Standards and Safety Act, 2000*, the Director under O. Reg. 209/01 (Elevating Devices) hereby orders, to protect and promote the safety of Ontarians, that pursuant to his power under section 14(2), any device that undergoes an alteration be used only in accordance with the requirements of this Order and that any alterations to any device be conducted in the manner set forth in this Order:

This Order should be read in conjunction with (the applicable Code), the CAD and the Guideline.

1.0 Alterations

All references are to the CSA B355:19 Platform lifts and stair lifts for barrier-free access (as amended by 295 / 22) except, references denoted with the ★ symbol (as defined in the Guideline) have been prefaced by the relevant **[B355 code reference]** to assist in locating / referencing the additional requirements in this document and on the alteration checklist.

In addition to Annex D of CSA B355:19, the Director orders that alterations (as applicable) comply with the following:

1.1 In addition to section D2.2 Alterations not covered, alterations shall comply with the following:

[D.2.2]★1 Where access restriction is added or removed to align with hazard assessed risk mitigations related to access and usage, the change to access restriction shall be submitted as:

- (a) a Minor A alteration (with schematic) where wiring changes to the device are involved;
- (b) a Minor B alteration where wiring changes to/on the device are not involved.

Note: The requirements in (a) do not include the addition of wiring for video or voice systems if they are not on the device.

1.2 In addition to section D.3.8 Landing doors and gates, alterations shall comply with the following:

[D.3.8.]★1 The removal of a door operator or gate is a minor B alteration.

This Directors Order becomes effective August 1, 2022.

Roger Neate.

Director, Ontario Regulation 209/01 (Elevating Devices), appointed under the *Technical Standards & Safety Act, 2000*

	1	2a	2b	2c	3	4	5	6
Conforms to B355	B355:19 Reference Number	Alteration Checklist for Director's Order 297/22 (see also Guideline 297/22) Scope of Alteration - B355:19 as amended by CAD 295/22 Part, Section or Requirement Job Reference:			Type of Alteration Work			
					Alteration		Replacement with	
					Modification Change	Addition	Same	Different Make/Mode
					Type of Submission Required			
X	D.2.1	General Alteration requirements						
X		requirements to acceptance inspection per Annex A						
X		A						
	D.2.2	Alterations not specifically covered in appendix D						
		D.2.2	Shall not reduce Level of safety below previously existing		consult TSSA engineering			
	[D.2.2] ★1	[D.2.2] ★1	change to access/usage restriction;		see below			
			a) includes wiring changes to the device		Minor A	Minor A		
			include schematic of changes					
			b) does not include wiring changes to the device		Minor B	Minor B		
	D.2.3	Welding						
		Welding of parts which support: car, drive m/c, trusses, girders, tracks			Major	Major		
		4.7	Welding Design					
			(a) Steel Structure, CSA W59					
			(b) Aluminum, CSA W59.2					
		6.6.1.6	Field Welding of pressure piping / fittings					
	D.2.4	Alteration Data Plate						
X		Data plate shall include						
X			a) name of contractor					
X			b) date of alteration					
X			c) applicable items in this Checklist (mark with X)					
X			d) edition of standard used for the alteration					
	D.3.1	Travel (Increase or Decrease)						
		Enclosed Vertical Platform Lift			Major	Major		
		Unenclosed Vertical Platform Lift			Major	Major		
		Stair Chair Lift			Major	Major		
		Stair Platform Lift			Major	Major		
		4.1.3	Protection against falling from the platform at landing					
		4.2.1	travel					
		4.2.3	Limit of travel					
		5.1.3	Unenclosed vertical platform lifts					
		5.3.	Mechanical Limits					
		5.4.1	Under-platform access					
		5.6.1	Guide Rails					
		7.2.5.	Safeties and Overspeed governor					
		7.2.5.2	Alternative safety device					
		7.6.2.1c)	Barrier Arm					
		7.7.3	Platform gate					
		8.4.4	Normal-terminal landing stopping device					
		8.5.3	final terminal-stopping switches					
	D.3.2	Line of travel inclination (change in inclination)						
		Stair Chair Lift			Major	Major		
		Stair Platform Lift			Major	Major		
		4.2.5	Inclination (angle not to exceed 45 degrees)					
		4.1.2b)	fall or tripping protection					
	D.3.3	Rated speed (change in)						
		change in rated speed			Major	Major		
		4.3	Rated Speed					
		6.6.5	Speed-limiting devices					
		7.2.5	Safeties and overspeed governor					
		9.1	Date Plate					

	1	2a	2b	2c	3	4	5	6
Conforms to B355	B355:19 Reference Number	Alteration Checklist for Director's Order 297/22 (see also Guideline 297/22) Scope of Alteration - B355:19 as amended by CAD 295/22 Part, Section or Requirement			Type of Alteration Work			
					Alteration		Replacement with	
					Modification Change	Addition	Same	Different Make/Model
		Job Reference:			Type of Submission Required			
	D.3.4	Capacity, rated load or carriage weight (change to)						
		Change in Capacity			Major	Major		
		Change in Rated Load			Major	Major		
		Change in carriage weight			Major	Major		
		Table 1 Capacity, rated load and size 4.5 Capacity, rated load and size 4.5.4 Display max. capacity and rated load on carriage 4.6 Safety factors ★ 5.6 Guide Rails ★ D.2.3 Welding 6.1.3 Drive unit brakes 6.6.2.2 Check valve 6.8 Friction drive 7.2.1. Carriage construction 7.2.5 Safeties and overspeed governor 7.3.1 Platform construction 9 Date Plate and signs						
	D.3.5	Platform size (change to)						
		change to platform size			Major	Major		
		Table 1 Capacity, rated load and size						
		4.4 Type of carriage (requirements changes based on carriage type)						
		4.6 Safety factors						
		D.2.3 Welding						
	D.3.6	Lighting						
		Alteration to lighting			Minor B	Minor A	mrr	Minor B
		4.8.1 Lighting illumination and location						
		4.8.2 Lighting for totally enclosed vertical platform lift						
		4.8.3 Emergency lighting						
	D.3.7	Runways						
		alteration to any portion of a runway enclosure wall			Major	Major		
		5.1.2 Enclosed vertical platform lifts						
		5.1.2(a) Minimum height of 1070 mm above the top landing						
		5.1.2(b) Conform to 5.1.1						
		5.1.2(c) equipped with landing doors or gate conforming to Clause 5.2.						
		5.1.3 Unenclosed vertical platform lifts						
		5.1.4 Enclosed stair platform lifts						
		5.5.1 Horizontal Clearance - vertical platform lifts						
		Lift added to existing enclosed runway			New			
		B355-19						
		5.5 Horizontal clearances						
	D.3.8	Landing doors and gates						
	D.3.8.1	alteration or replacement to a landing door or gate			Minor B	Minor A	Minor B	
		★ 4.1.4.4 Projections from the internal surfaces						
		5.2.1.1 strength, vision panel, and fire rating						
		5.2.2 height and width						
		5.2.3 door or gate interlock						
		5.2.4 testing and certification of Interlocks / locks						
	D.3.8.2	power added to a door or gate			Minor A	Minor A	Minor B	
		5.2.1.3 (a) timing from close to fully open of swing doors/gates						
		5.2.1.3 (b) force to stop the movement of the swingdoors/gates						
		8.1.1 electrical equipment and wiring meets Section 38 OESC						
		8.1.2 electrical equipment meets B44.1/A17.5						
	[D.3.8.]★1	Remove door/gate operator			Minor B			

		1	2a	2b	2c	3	4	5	6
Conforms to B355	B355:19 Reference Number	Alteration Checklist for Director's Order 297/22 (see also Guideline 297/22) Scope of Alteration - B355:19 as amended by CAD 295/22 Part, Section or Requirement				Type of Alteration Work			
						Alteration		Replacement with	
						Modification Change	Addition	Same	Different Make/Model
		Job Reference:				Type of Submission Required			
	D.3.9	Door or gate interlock							
		Door or gate interlock is altered							
		Replacement/addition of interlock with the different type (fixed or retiring cam or solenoid)				Minor A	Minor A	mrr	Minor A
		5.2.3	door or gate interlock,						
		5.2.4	testing and certification of Interlocks / locks						
		5.2.5.11	Examination of operation (engagement)						
		8.3.3.3	doors or gates openable within 50mm of landing						
		8.4.2	Protection in case of failure (solenoid interlock)						
		8.5.8	Door or gate interlock contacts						
		8.1.1	electrical equipment and wiring meets Section 38 OESC						
		8.1.2	electrical equipment meets B44.1/A17.5						
	D.3.10	Under platform (pit)							
		underplatform alteration							
		a) pit drains and sumps				Minor A	Minor A		
		5.4.2 f)	prevent ground water entry						
		5.4.2 g)	drains and sumps to the plumbing code						
		b) pit access				Minor A	Minor A		
		5.4.2	Under-platform access (where pit >300mm deep)						
		c) pit illumination				Minor B	Minor B		
		4.8	Lighting						
		d) pit stop switch				Minor A	Minor A		
		8.5.9	Runway stop device						
		e) pit depth				Minor B	Minor B		
		5.4.2	Under-platform access (where pit >300mm deep)						
		f) access to underside of platform				Minor B	Minor B		
	D.3.11	Drive unit (drive unit is altered)							
		All Drive unit				Major		mrr	Major
		6.1	Requirements for all drive units						
		6.1.6	Drive unit enclosure						
		8.1	Electrical equipment - General						
	D.3.12	Manual moving of carriage in case of emergency							
		manual moving of carriage is altered or added				Major	Major	mrr	Minor B
		6.1.4.1	not accessible inside						
		6.1.4.2	smooth hand wheel						
		6.1.4.3	instructions						
		6.1.4.4	direction indications						
		6.1.4.5	brake release						
		6.1.4.6	safe and convenient access						
		6.1.4.7	means to prevent automatic operation						
		8.5.11	Manual moving device switch						
	D.3.13	Suspension wire rope							
		Change no. of ropes				Major	N/A		
		Change in rope material							
		Change in rope diameter							
		6.2.1	Suspension wire rope						
		6.2.2	Winding Drum						
		6.2.3	Sheaves						
		8.5.5	Slack belt or chain drive, drum, sheave, and safeties switches						
	D.3.14	Suspension chain							
		Change to a different material				Major	N/A		
		Change to a different size				Major	N/A		
		6.4.1.2	roller chain to B29.100						
		6.4.1.3	Link strength equal chain strength						

	1	2a	2b	2c	3	4	5	6
Conforms to B355	B355:19 Reference Number	Alteration Checklist for Director's Order 297/22 (see also Guideline 297/22) Scope of Alteration - B355:19 as amended by CAD 295/22 Part, Section or Requirement Job Reference:			Type of Alteration Work			
					Alteration		Replacement with	
					Modification Change	Addition	Same	Different Make/Model
					Type of Submission Required			

1		2a	2b	2c	3	4	5	6
Conforms to B355	B355:19 Reference Number	Alteration Checklist for Director's Order 297/22 (see also Guideline 297/22) Scope of Alteration - B355:19 as amended by CAD 295/22 Part, Section or Requirement			Type of Alteration Work			
					Alteration		Replacement with	
		Modification Change	Addition	Same	Different Make/Model	Type of Submission Required		
	D.3.15	Hydraulic equipment						
		a) Power unit and pump			Minor A		Minor B	Minor B
		6.6	Hydraulic drive					
		6.6.1	General requirements					
		6.6.2	Valves					
		6.6.3	Piping requirements					
		6.6.4	Connections and fittings					
		6.6.5	Speed-limiting devices					
		6.6.6	Levelling device, anti-creep					
		6.6.7	Safety bulkhead					
		6.6.8	Pressure Sensor					
		6.6.9	Telescopic plunger guides					
		6.6.10	Operation dependent on electric power supply					
		8.1	Electrical equipment - General					
		8.1.1	electrical equipment and wiring meets Section 38 OESC					
		8.1.2	electrical equipment meets B44.1/A17.5					
		b) Hydraulic jack			Major		MinorA	Major
		6.6.1	General requirements for components under fluid pressure					
		c) Plunger			Major		Minor A	Minor A
		6.6.1.1	Factor of safety					
		6.6.1.2	Material					
		6.6.1.4	Component proof test					
		6.6.1.5	Component markings					
		6.6.1.6	Field welding					
		6.6.9	Telescopic plunger guides					
		d) Cylinder			Major		Minor A	Minor A
		6.6.1.1	Factor of safety					
		6.6.1.2	Material					
		6.6.1.4	Component proof test					
		6.6.1.5	Component markings					
		6.6.1.6	Field Welding of pressure piping / fittings					
		6.6.4.2	Grooved pipe fittings					
		6.6.7	Safety bulkhead					
		e) Increase working pressure			Major			
		6.6.1.3	Working Presssure					
		6.6.1.4	Component proof test					
		6.6.1.5	Connection and fitting					
		6.6.1.6	Field Welding of pressure piping / fittings					
		6.6.1.7	Flexible hose and fitting assemblies					
		6.6.2	Valves					
		6.6.3	Piping Requirements					
		6.6.4	Connections and fittings					
		6.6.5	Speed-limiting devices					
		6.6.6	Levelling device, anti-creep					
		6.6.7	Safety Bulkhead					
		6.6.8	Pressure Sensor					
		6.6.9	Telescopic plunger guides					
		f) Valves, pressure piping, and fittings			Major		Minor B	Minor B
		6.6.1	General requirements for components under fluid pressure					
		6.6.2	Valves					
		6.6.3	Connection and fittings					
		6.6.4	Connections and fittings					
		6.6.5	Speed-limiting devices					
		6.6.6	Levelling device, anti-creep					

	1	2a	2b	2c	3	4	5	6
Conforms to B355	B355:19 Reference Number	Alteration Checklist for Director's Order 297/22 (see also Guideline 297/22) Scope of Alteration - B355:19 as amended by CAD 295/22 Part, Section or Requirement			Type of Alteration Work			
					Alteration		Replacement with	
					Modification Change	Addition	Same	Different Make/Model
		Job Reference:			Type of Submission Required			
		6.6.8	Pressure Sensor					
		6.6.10	Operation dependant on electric power supply					
		g) Pipes and hoses			Minor A	Minor A	Minor B	Minor B
		6.6.1	General requirements for components under fluid pressure					
		6.6.3	Piping Requirements					
		6.6.4	Connections and fittings					
		h) Pressure sensor				Minor A	mrr	Minor A
		6.6.8	Pressure sensor					
		i) Speed-limiting devices			Minor B	Minor B	mrr	Minor B
		6.6.5	Speed-limiting devices					
	D.3.16	Electrical equipment						
		8	Controller and EPD		Major		Major	Major

	1	2a	2b	2c	3	4	5	6
Conforms to B355	B355:19 Reference Number	Alteration Checklist for Director's Order 297/22 (see also Guideline 297/22) Scope of Alteration - B355:19 as amended by CAD 295/22 Part, Section or Requirement			Type of Alteration Work			
					Alteration		Replacement with	
		Job Reference:		Modification Change	Addition	Same	Different Make/Model	
		Type of Submission Required						
Tests Mark with 'X'	B355:19 Reference Number	Indicate which Annex A testings are required for the specified Alteration Scope from Above						
	A.2 a) GENERAL							
	i) Hazards							
	4.1.1	General - no defects, adequate strength, suitable quality						
	4.1.2	Protection against hazards						
	4.1.3	Protection against falling from the platform at landing						
	4.1.4	Obstructions and projections						
	ii) Travel							
	4.2.1	Travel						
	4.2.3	Limits of travel						
	iii) Floor Penetration							
	4.2.2	Travel						
	4.2.3							
	iv) Data Plate and Signs							
	9	Data plate and signs						
	9.1	Data plate						
	9.2	Under-platform sign						
	9.3	Markings of data plate and sign						
	9.4	Markings of landing zone for an enclosed vertical platform lift						
	A.2 b) DRIVE							
	i) Rated Speed							
	4.3	Rated Speed						
	ii) Power Transmission							
	6.1.2	Power Transmission						
	iii) Brake with 125% rated load							
	6.1.3	Drive unit brakes						
	iv) Enclosure							
	6.1.6	Drive unit enclosure						
	v) type of drive, additional							
	6.2	Suspension wire rope, winding drums, sheaves, protection and guarding, and traction						
	6.3	Rack and pinion drive						
	6.4	Chain and chain sprocket drive						
	6.5	Screw and nut drive						
	6.6	Hydraulic drive						
	6.7	Rope chain and rope sprocket drives						
	A.2 c) RUNWAY							
	i) Enclosure							
	5.1	Runway enclosures						
	ii) Landing Doors and Gates							
	5.2	Landing doors and gates						
	8.5.8	Door or gate interlock contacts						
	iii) Mechanical Limits							
	5.3	Mechanical limits						
	iv) Under-platform access							
	5.4	Under-platform access						
	v) Guide Rails							
	5.6	Guide rails						
	vi) Guards at Ceilings							
	5.7	Stair lift guards at ceiling intersections						

	1	2a	2b	2c	3	4	5	6
Conforms to B355	B355:19 Reference Number	Alteration Checklist for Director's Order 297/22 (see also Guideline 297/22) Scope of Alteration - B355:19 as amended by CAD 295/22 Part, Section or Requirement			Type of Alteration Work			
					Alteration		Replacement with	
					Modification Change	Addition	Same	Different Make/Model
		Job Reference:			Type of Submission Required			
	A.2 d)	CARRIAGE						
	i)	Capacity, Rated Load, and Size						
		4.5	Capacity, rated load, and size					
	ii)	Enclosure						
		7.5.3	Guard (enclosure) - Standing platform					
		7.6.2	Guard (enclosure) - Wheelchair platform					
		7.7.2	Guard (enclosure) - Wheelchair-and-attendant platform					
	iii)	Sensitive Edges or Surfaces						
		7.2.4	Sensitive edges or sensitive surfaces					
		8.5.4	Sensitive edge and sensitive surface switches					
	iv)	Safeties with 125% rated load						
		7.2.5.1 c)	Safeties shall be capable of stopping and holding the carriage loaded with 125% of the rated load					
		8.5.5	Slack belt or chain drive, drum, sheave, and safeties switches					
	v)	Foldable Components						
		7.2.6.2	Stair platform lifts with foldable or movable components (except the seat) shall be incapable of being started					
		8.5.6	Foldable, rotatable, or hinged component contacts					
	vi)	Rotatable Chair						
		7.4.3.1	If a chair is rotatable, an electrical protective contact conforming to Clause 8.5.6 shall be provided					
		8.5.6	Foldable, rotatable, or hinged component contacts					
	vii)	Barrier						
		7.6.2.1 c)	Unenclosed stair platform lift - have retractable passenger restraining arms					
		8.5.7	Gate and passenger restraining arm contacts					
	viii)	Gate						
		7.7.3	Platform gate					
		8.5.7	Gate and passenger restraining arm contacts					
	ix)	Safety Flaps						
		7.6.3	Rollaway protection					
		7.6.5	Ramps, flaps, and hinged-edge stops					
		8.5.6	Foldable, rotatable, or hinged component contacts					
	x)	Handgrips or Handrails						
		7.5.2	Handgrips					
		7.7.5	Handrails					

	1	2a	2b	2c	3	4	5	6
Conforms to B355	B355:19 Reference Number	Alteration Checklist for Director's Order 297/22 (see also Guideline 297/22) Scope of Alteration - B355:19 as amended by CAD 295/22 Part, Section or Requirement			Type of Alteration Work			
					Alteration		Replacement with	
					Modification Change	Addition	Same	Different Make/Model
		Job Reference:			Type of Submission Required			
	A.2 e)	CLEARANCES						
		i) Vertical						
		4.1.5	Vertical clearance					
		ii) Horizontal						
		5.5	Horizontal clearances					
		7.2.3.2	Protection on carriages - clearance of not less than 50 mm from any part of the fixed installation					
		iii) at Landings						
		7.5.4	Clearances at landings - Standing platform					
		7.6.4	Clearances at landings - Wheelchair platform					
		7.7.4	Clearances at landings - Wheelchair-and-attendant platform					
	A.2 f)	ELECTRICAL EQUIPMENT						
		i) Voltage and Current Reading						
		5.2.4.1.2 c) iii)	The following marking requirements shall apply: rated voltage and current (ac or dc)					
		5.2.4.2.	Connections for and test of electrical parts					
		5.2.5.3.2	AC-rated locking devices shall have their electrical parts connected to an inductive circuit ...					
		5.2.5.3.3	DC-rated locking devices shall have their electrical parts connected to an inductive circuit...					
		5.2.5.7	Insulation test					
		ii) Voltage, Fuses, Disconnecting Means						
		8.1	Electrical equipment and wiring shall conform to...					
		iii) Operating Devices						
		8.2	Operation and operating devices					
		iv) Alarm and Warning Signals						
		8.3	Alarm and warning signal					
		v) Control Equipment						
		8.4	Control and control equipment					
		vi) Emergency Stop Device						
		7.3.2 b)	Platform ceilings - solid and capable of sustaining a load of..					
		8.5.2	Emergency stop device					
		8.5.9	Runway stop device					
		vii) Final Terminal-Stopping Devices						
		8.5.3	Final terminal-stopping switches					